



F40 CONTROL VALVES

- Ideal for filter applications
- Choice of 12 day clock, manual or meter
- Consistent brining regardless of salt levels with timed brine refills
- Solid brass valve body for superior strength and durability

F40 SERIES CONTROL VALVES

FLOTROL F40 CONTROL VALVES

Are fully adjustable 5 cycle valves that deliver controlled backwash, slow rinse and downflow bringing, rapid rinse, downflow service and timed brine refill.

Backwash capacity can handle up to 30" in diameter tanks. The Flotrol F40 has a solid valve body for high durability and superior strength.

FLOTROL F40 CONTROL VALVES

Come with 12 day clock, manual or meter and offer consistent brining regardless of salt levels through timed brine refills. They incorporate a hydraulically balanced piston, seal and spacer design and are ideal for filter applications. The 1 1/2" top mount control valve is ideal for small commercial and industrial applications and have continuous flow rate of 51 gpm with a backwash of 49 gpm.



F40 SERIES CONTROL VALVES

TYPICAL APPLICATIONS


WATER SOFTENER	10" - 30" DIAMETER
IRON FILTER	10" - 24" DIAMETER
SEDIMENT FILTER	10" - 24" DIAMETER
CARBON FILTER	10" - 24" DIAMETER
NEUTRALIZING FILTER	10" - 24" DIAMETER

F40 SERIES

PART NUMBER	DESCRIPTION	CASE QUANTITY	BOX DIMENSION (INCHES)	WEIGHT
F40SM110V60HZ	(F40SMH312L3U4TC1-1),F40 SOFTENER METER 110v/60hz	1	16" X 13" X 14"	32 LBS
F40ST110V60HZ	(F40STA312L3U4TN1-1),F40 SOFTENER TIMER 110v/60hz	1	16" X 13" X 14"	26 LBS
F40FT110V60HZ	(F40FTENNN3U4TN1-1),F40 FILTER TIMER 110v/60hz	1	16" X 13" X 14"	26 LBS
F40SM220V60HZ	(F40SMH312L3U4TC5-1),F40 SOFTENER METER 220v/60hz	1	16" X 13" X 14"	32 LBS
F40ST220V60HZ	(F40STA312L3U4TN5-1),F40 SOFTENER TIMER 220v/60hz	1	16" X 13" X 14"	26 LBS
F40FT220V60HZ	(F40FTENNN3U4TN5-1),F40 FILTER TIMER 220v/60hz	1	16" X 13" X 14"	26 LBS

PART NUMBER ORDERING GUIDE

PART NUMBER ORDERING GUIDE



DISTRIBUTED BY:



P.O. Box 2637 Chino Hills, CA 91709 USA
sales@Liquatec.com
www.Liquatec.com